


5MP+5MP HD Outdoor Dual lens PT Wi Fi Camera

Uho-P2S-M55F34



Features

- Fixed camera and PTZ camera integration, dual channels with one IP, look at overall situation and consider details at the same time
- Ultra 265, H.265, H.264
- Support digital WDR (Wide Dynamic Range)
- Built in Mic & Speaker, support two way audio, offer better interaction
- Support sound and light warning, makes warning and alarming more noticeable
- Smart IR, up to 30 m (98 ft) IR and 10m (33ft) warm light distance, suitable for more scenes
- IR & warm light illumination to deal with different scenes and achieve full color illumination
- Supports 512 GB Micro SD card
- Wi Fi connection and easy installation
- IP66 ingress protection

Specifications


Channel	Panorama	Detail
Camera		
Sensor	1/3.0" CMOS	

Min. Illumination	Colour: 0.003 lux (F1.6, AGC ON) 0 lux with IR	
Day/Night	IR-cut filter with auto switch (ICR)	
Shutter	Auto/Manual, 1 to 1/100000 s	
S/N	> 52 dB	
WDR	DWDR	
Lens		
Digital Zoom	N/A	4X
Iris	F1.6	
Field of View (H)	94.9°	80.6°
Field of View (V)	53.7°	44.8°
Field of View (D)	100.5°	86.7°
Lens Type	Fixed	
DORI		
DORI Distance (Lens)	2.8mm	4.0mm
DORI Distance (Detect)	63.0 (206.7ft)	90.0 (295.3ft)
DORI Distance (Observe)	25.2 (82.7ft)	36.0 (118.1ft)
DORI Distance (Recognize)	12.6 (41.3ft)	18.0 (59.1ft)
DORI Distance (Identify)	6.3 (20.7ft)	9.0 (29.5ft)
Illuminator		
Light On/Off Control	Auto/Manual	
Illumination Distance (IR)	10 m (32.8 ft.)	30 m (98.4 ft.)
Illumination Distance (Warm Light)	10 m (32.8 ft.)	30 m (98.4 ft.)
Wavelength	850 nm	
Video		
Frame Rate-Main Stream	5MP (2880*1620), Max 15fps; 4MP (2560*1440), Max 15fps; 3MP (2304*1296), Max 15fps; 2MP (1920*1080), Max 15fps; 720P (1280*720), Max 15fps;	
Frame Rate-Sub Stream	640*360, Max 15fps; 2CIF (704*288), Max 15fps; CIF (352*288), Max 15fps;	
Video Compression	Ultra 265, H.265, H.264	
Video Bit Rate	128 Kbps to 2048 Kbps	
OSD	Up to 8 OSDs	
Privacy Mask	Support (only NVR)	
ROI	Up to 8 areas	
Video Stream	Dual streams	
Image		
White Balance	Auto, Outdoor, Fine tune, Sodium lamp, Locked, Auto2	
Digital Noise Reduction	2D/3D DNR	
Smart IR	Support	
Flip	Normal, Flip vertical, Flip horizontal, 180°	
HLC	N/A	

BLC	N/A
Defog	Digital defog
Events	
Basic Detection	Motion detection, Ultra motion detection, Tampering alarm, High-Decibel detection
General Function	IP address filtering, Access policy, ARP protection, RTSP authentication, User authentication, HTTP authentication
Audio	
Audio Compression	G.711U, G.711A
Audio Bitrate	64 Kbps
Two-way Audio	Support
Suppression	Support
Sampling Rate	8 kHz
Storage	
Edge Storage	MicroSD, up to 512 GB
Network Storage	ANR
Network	
Wi-Fi	2.4G Wi-Fi (IEEE802.11b/g/n/ax), built-in antenna
Protocols	IPv4, TCP, UDP, DHCP, RTSP, DNS, DDNS, NTP, HTTP, ICMP, ARP, UPnP
Compatible Integration	API
Client	Uniarch client, Uniarch app
Web Browser	Plug-in required live view: IE 10+, Chrome 45+, Firefox 52+, Edge 79+
Wi-Fi	
Wireless Standards	IEEE802.11b/g/n/ax
Frequency Range	2.4 GHz to 2.4835 GHz
Channel Bandwidth	20/40 MHz Support
Modulation Mode	802.11b: CCK 802.11g/n: OFDM 802.11ax: OFDMA
Wi-Fi Security	64/128-bit WEP, WPA-PSK/WPA2-PSK
Transmit Power	802.11b: 17±1.5 dBm@11 Mbps802.11g: 16±1.5 dBm@54 Mbps802.11n: 16±1.5 dBm@MCS7802.11ax: 16±1.5 dBm@MCS9
Receive Sensitivity	802.11b: -76 dBm@11 Mbps (Typical)802.11g: -65 dBm@54Mbps (Typical)802.11n: -61 dBm@MCS7, HT40 (Typical)802.11ax: -54 dBm@MCS9, HE40 (Typical)
Transmission Rate	802.11b: 11 Mbps802.11g: 54 Mbps802.11n: up to 150 Mbps802.11ax: up to 270 Mbps
Interface	
Video Output	N/A
Built-in Mic	Support
Built-in Speaker	Support
WIFI	Support
Network	1 × RJ45 10 M/100 M Base-TX Ethernet
PTZ	
Pan Range	-150° ~ 150°0° ~ 350°

Pan Speed	N/A	1°/s ~ 40°/s Preset speed: 40°/s
Tilt Range	-5° ~ 30°	0° ~ 90°
Tilt Speed	N/A	1°/s ~ 30°/s Preset speed: 30°/s
Number of Presets	20	
Certification		
EMC	CE EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 50130) FCC (FCC 47 CFR part15 B)	
RF	FCC ID (FCC CFR 47 part15 C) CE RED (EN 301 489-1, EN 301 489-17, EN 300 328, EN 62311)	
Safety	CE LVD (EN 62368-1)	
Environment	CE-RoHS (2011/65/EU; (EU) 2015/863) ; WEEE (2012/19/EU)	
Protection	IP66 (IEC 60529)	
General		
Power Consumption	MAX 11.5W	
Power	DC 12V ± 25%	
Power Interface	Ø5.5 mm coaxial power plug	
Dimensions	Φ117mm*157mm*202mm (Φ4.6”x 6.2”x 7.9”)	
Weight	0.62kg (1.36lb)	
Working Environment	-30 °C to 60 °C (-22 °F to 140 °F), Humidity: ≤ 95% RH (non-condensing)	
Storage Environment	-30 °C to 60 °C (-22 °F to 140 °F), Humidity: ≤ 95% RH (non-condensing)	
Surge Protection	4 KV	
Reset Button	Support	
LED Indicator	1, red/blue	

Dimensions



Zhejiang Uniview Technologies Co., Ltd.



<http://www.uniview.com>



overseasbusiness@uniview.com; globalsupport@uniview.com



No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China



©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.

*Despite our best efforts, technical or typographical errors may exist in this document.

Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.